

# Broadband Multi-layered Radar Absorbing Paint (KV-Paint-2L-418)

### **FEATURES:**


- It is multi-layered radar absorbing paint where broad-band impedance matching is carried out by tapering electrical and magnetic properties and thickness of different layers.
- Thickness of paint is around 4.5 mm and weight around 8 kg/m2.

#### **DESCRIPTION:**

• Ultra wide band Multi- Layered Radar absorbing paint for ship borne applications.

#### **TYPICAL PERFORMANCE:**

- Effectively, the paint provides RCS Reduction of minimum 7 dB and typically average RCS Reduction is 10 dB from 4 to 18 GHz.
- Operating Frequency: 4 GHz 18 GHz



## **GLOBAL PRESENCE**







## SLTL'S STRENGTH

**Experience** Mfg. Plants **Exports Laying Over** Sq. mtr. **Yearly R&D Countries** 9001-2015 **Systems Awards Patents** 



C E An ISO 9001:2015 Certified Company

#### Sahajanand Laser Technology Ltd. (SLTL Group)

E-30, Electronic Estate, G.I.D.C., Sector - 26, Gandhinagar - 382 028, Gujarat, India. Tel : +91-79-6170-1616 | Fax : +91-79-2328-7470

+91-90-9907-1094 | microwave@SLTL.in



www.**SLTmicrowave**.com